OLYMPUS®

FCON-T01
TCON-T01

JP 取扱説明書

取り付け方

カメラの取扱説明書をご覧ください。

使用上の注意

- 急激な温度変化で曇り(結露)が発生する場合があります。
- フラッシュ使用時、レンズの影が映りこんだり、画面周辺部が暗くなる場合があります。
- 使用条件によりAF、AE、IS等は本来の動作・性能を発揮しない場合があります。
- カメラを専用の設定にしてご使用ください。
- 水中でのご使用後はすぐに真水で異物や塩分を洗い落としてください。
- 洗浄等で薬品類を使わないでください。

ご注意 必ずお読みください

⚠ 警告 安全上のご注意

- レンズで太陽を見ないでください。失明や視力障害を起こすことがあります。
- レンズキャップを付けずに放置しないでください。太陽光が焦点を結んで故障や火災の原因になることがあります。
- カメラに取り付けた状態でレンズを太陽に向けないでください。太陽光が焦点を結んで故障や火災の原因になることがあります。

主な仕様	FCON-T01	TCON-T01
倍率	0.74倍	1.7倍
質量(キャップ除く)	125g	94g
大きさ(最大径×全長)	φ65x27.2mm	φ46.2x43.3mm
防水	保護等級8級(IPX8):JISC0920/IEC60529相当(当社試験方法による) 水深20m/60分以内	
防塵	保護等級6級(IP6X):JISC0920/IEC60529相当(当社試験方法による)	
使用温度/保存温度	−10℃〜40℃	

外観・仕様は改善のため予告なく変更することがありますので、ご了承ください。
詳細は、http://www.olympus.co.jp/からご覧ください。
0120-084215　携帯電話・PHSからは TEL:042-642-7499

EN INSTRUCTIONS

Mounting lens parts

Refer to the instruction manual of your camera.

Notes on Using

- When using a flash, the shadow of the lens may appear in images or the periphery of the display may darken.
- The functions of the lens including AF, AE and IS may not show their true operation or performance in some conditions of use.
- It is recommended to use the special setting for those lens.
- Be sure to wash any foreign materials and salts by fresh water.
- Do not use chemicals for cleaning.

Precautions: Be Sure to Read the Following

⚠ Warnings: Safety Precautions

- Do not directly view the sun through the lens. It may cause blindness or vision impairment.
- Do not leave the lens without the cap. If solar light is converged through the lens, a fire may result.
- Do not point the camera lens at the sun. Sunlight will converge in the lens and focus inside the camera, possibly causing a malfunction or fire.

Main specifications	FCON-T01	TCON-T01
Magnification	0.74x	1.7x
Weight (Excluding the cap)	125 g (4.4 oz.)	94 g (3.3 oz.)
Dimensions (Max. dia. × Overall length)	Ø 65 (2.6 in.) × 27.2 mm (1.1 in.)	Ø 46.2 (1.8 in.) × 43.3 mm (1.7 in.)
Water resistance	Equivalent to IEC Standard publication 529 IPX8 (under OLYMPUS test conditions) Available in 20 m (65.6 feet) deep water/Within 60 minutes	
Dust resistance	IEC Standard publication 529 IP6X (under OLYMPUS test conditions)	
Use/Storage temperature	-10°C to 40°C (14 °F to 104 °F)	

Specifications are subject to change without any notice or obligation on the part of the manufacturer.
For additional information visit: http://www.olympus.com/

OLYMPUS®

© 2012 OLYMPUS IMAGING CORP.

VM377301
Printed in China